



230_{VAC}



24VDC

PREMIER
PREMIER24

ARTICULATED ARM

personalised release key

up to 4.0 m



CONTROL UNITS:

PR.45E	└───┐	BRAINY	📄 134
		HEADY	📄 135
PR.45EL	└───┐	BRAINY	📄 134
		HEADY	📄 135
PR.45E24	└───┐	BRAINY24+	📄 143
		BRAINY24	📄 144

Irreversible geared motor suitable for gates installed on large columns, available in 230 Vac and 24 Vdc versions. Built-in electromechanical open and close limit switches, with sturdy articulated anti-shearing arm in galvanised steel.



Arm not included

230 Vac

- Irreversible 230 Vac electromechanical geared motor also available in the PR.45EL version for large doors

24 Vdc | intensive use

- Irreversible 24 Vdc geared motor for intensive use
- Amperometric sensor obstacle detection system to prevent crushing
- Optional battery powered operation



A (mm)	B (mm)	C (mm)	D (mm)
50	883	277	429
150	851	181	466
200	828	117	475
250	800	32	469
300	846	28	468

COMPLETE KITS



MOTORS



CONTROL UNIT



ARMS



PHOTOCELLS



FLASHING LIGHT



SELECTOR



TRANSMITTER

KPR	2x PR.45E	1x HEADY	2x DU,E2	1x PUPILLA,R	1x LAMPI,LED	1x TOKEY	1x TO.GO2VA
KPR.24	2x PR.45E24	1x BRAINY24	2x DU,E2	1x PUPILLA,R	1x LAMPI24.LED	1x TOKEY	1x TO.GO2VA

**DU.E2**

Single galvanized steel arm.

**MB.SE**

Externally fitted anti-intrusion cable unlock device which allows the gate to be unlocked from outside.

**DU.V96**

12 Vac/dc vertical electric lock, supplied with counterplate. Permits internal/external release.

**DU.V90**

12 Vac/dc horizontal electric lock, supplied with counterplate. Permits internal/external release.

**DU.9990**

Covering plate for DU.V90.

**E.LOCK**

230 Vac vertical electric lock, supplied with counterplate.

**E.LOCKSE**

Extended cylinder for E.LOCK electric lock. It allows unlocking gates up to 55mm-thick from the outside.

**ID.TA**

Warning board.

**IRI.TX4VA**

4-channel transmitter with Advanced Rolling Code and Rolling Code.

**IRI.TX4AK**

4-channel transmitter with Advanced Rolling Code and Fixed Code.

**IRI.LAMP**

White full range flashing light, 20-255 VAC with built-in aerial.

**IRI.KPAD**

Battery operated wireless vandal-proof digital keypad with alert buzzer and backlit buttons. Triple coding: Rolling Code, Programmable Code and Advanced Rolling Code. 254 memorisable codes.

**IRI.CELL**

Pair of vandal-proof metal covers for PUPILLA/PUPILLA.R photocells, comprising front and rear shells with concealed screw. They can maintain perfect orientation over 180°.

**PUPILLA**

Pair of photocells adjustable to 180°. Option to synchronise up to 4 pairs, 24 VAC/DC power supply. Easy adjustment through a LED that signals optimal alignment. Compact size: 36x110x35 mm

**BRAINY24.CB-SW**

Accessory equipped with 1.2 Ah batteries and support bracket.

**BRAINY24.CB**

Accessory with CBY.24V battery charger, 1.2 Ah batteries and support bracket.

TECHNICAL DATA	PR.45E*	PR.45EL	PR.45E24*
Power supply	230 Vac (50-60Hz)	230 Vac (50-60Hz)	230 Vac (50-60Hz)
Motor supply	230 Vac	230 Vac	24 Vdc
Max absorbed current	1.75 A	1.45 A	9 A
Torque	325 Nm	300 Nm	320 Nm
Opening time	13"	20"	9"
Duty cycle	30%	30%	intensive use
Protection level	IP44	IP44	IP44
Operating temperature	-20°C /+50°C	-20°C /+50°C	-20°C /+50°C
Leaf max dimension	3 m	4 m	3 m
Weight	10.5 kg	10.5 kg	9 kg
Items no, per pallet	42	42	42
Kit weight	34.6 kg	---	34 kg
Kits no, per pallet	12	---	12

* Available in 115 VAC version